



# TKB 12



- the safe way!

## TKB 12

*TKB 12 is Epoke's series of robust towed spreaders, all with a large action radius.*

*The dosing system is a well-known Epoke method, which ensures precise and uniform delivery of salt, sand and grit.*

*The spreaders are fully speed-compensated and thus always deliver the set amount of spreading material per m<sup>2</sup> regardless of changes in speed.*

TKB 12 spreaders are simple, strong and stable, developed for the treatment of icy roads using dry matter. The spreaders easily handle difficult materials such as sand and salt which clumps, and grit. TKB 12 is usually towed by a truck or tractor, whose load capacity is the only limitation for the spreader's action radius. TKB 12 is fitted close to the towing vehicle and at the same time is equipped with guide chains, which ensure that the spreader does not come into contact with the towing vehicle when the driver reverses, turns or drives around bends. This means greater safety on the road and comfort for the driver.

The limited distance between the road surface and the spreader's distributor roller limits sensitivity to side-wind and turbulence. The spreading material is thus

spread precisely on the road surface with the optimal spreading profile.

The Epoke method is a well-known and well-proven dosing system, where the distributor roller and agitator are driven by the spreader's drive wheel via mechanical gearing. The agitator crushes any clumps of salt or sand and via a spring-loaded base, the distributor roller applies the material.

The distributor roller is manually coupled to the machine or via an electrical or pneumatic remote control in the driver's cab.

TKB 12 spreaders are robust, with long lifetimes and low maintenance costs.

“

### Special benefits:

- ▣ TKB 12 spreaders are ideally suited for use with difficult materials
- ▣ The spreader's action radius is only limited by the truck's load capacity
- ▣ The spreading profile is perfect thanks to limited wind sensitivity
- ▣ This well-known series has proved its value in the field for many years

”

**TKB 12 is available in two different versions, the TKB12-260 and TKB12-280:**

	TKB12-260	TKB12-280
Volume of hopper (m <sup>3</sup> )	1.1	1.2
Total width (mm)	2,600	2,800
Min. spreading width (mm)	2,200	2,500
Deadweight (kg)	670	710
<b>Standard equipment</b>	Agitator Distributor roller Solid support wheel Drawbar Guide chains Manual connection and disconnection 12-ply tyres with steel insert	
<b>Extra equipment</b>	Remote control (electrical or pneumatic controlled) Lights Rubber front edge Spray guard Roller made from high-strength Hardox steel	

TKB 12 spreaders are sandblasted and surface treated with a zinc dust primer and 2-component topcoat. The spreaders are thus well protected against rust.



*The spreader's adjustable support wheel makes it easy to attach or detach the spreader from the truck.*



*The Epoke dosing system consists of an agitator and a spring-loaded distributor roller.*



*The dosing scale regulates the amount of deposited material via the connection to the spring base adjustment.*



*Built-in rear lights.*

## EPOKE GROUP

We produced our first sand and salt spreader in 1955, and since then we have solely focused on the development, production and sale of machines and equipment for the treatment of icy roads. Today, we are a global leader. In Denmark, sales are carried out by our own sales staff, while abroad our subsidiaries and 31 dealers manage sales.

Learn more at [www.epoke.dk](http://www.epoke.dk)

Epoke A/S  
Vejenvej 50  
6600 Vejen, Denmark  
[www.epoke.dk](http://www.epoke.dk)

