$\leftarrow \ \, \underline{\text{HOME}} \leftarrow \ \, \underline{\text{FLOOR GRINDERS}} \text{BG 250}$

Husqvarna BG 250













WEIGHT

- Aggressive grinding
- Efficient dust management
- Easy to transport
- ✓ Versatile

FLOOR GRINDER BG 250 3x400V 5.5kW 50Hz | EU Art nr: 970 61 49-01

GET A QUOTE



Product details for BG 250

very easy and comfortable to use with low vibrations. Thanks to its two front handles, it is possible to lift the machine up a flight of stairs. BG 250 has an asymmetric dust exhaust with a built-in deflector for improved/optimised dust extraction. In addition, it is equipped with a special drive system for optimum load distribution.

× FEATURES

Discover all features and learn more about the benefits

SHOWING 4 FEATURES

AGGRESSIVE GRINDING

The single grinding head allows all the pressure of the machine to be distributed onto the one diamon...

EFFICIENT DUST MANAGEMENT

This grinder is equipped with a 76 mm diameter dust hose connection for minimised dust exposure...

EASY TO TRANSPORT

Thanks to its two front handles, it is possible to lift this single disc grinder up flights of stairs.

VERSATILE

This floor grinder has several optional grinding discs for use in specific applications.

× TECH DATA TABLE

Get full product details and all technical specifications

TOP SPECIFICATIONS

Output power 5.5 kW

Grinding width 250 mm

GINE tiput power (As rated by the engine/motor manufacturer) 5.5 kW tiput power wer source Electrical TOTOR Inding Equipment Inding width 250 m mber of grinding discs inding disc speed max 1,920 HER pe of operation Push MENSIONS se diameter roduct size length oduct size length oduct size height 1,006 m 1,	SHOW LESS ^	
GINE ttput power (As rated by the engine/motor manufacturer) ttput power ttput	d level	83 dB(A)
Signs tiput power (As rated by the engine/motor manufacturer) 5.5 kW tiput power 5.5 kW wer source Electr TOR Itage 400 V 16 A INDING EQUIPMENT Inding width 250 m mber of grinding discs 1 inding disc speed max 1,920 HER pe of operation Push MENSIONS se diameter 76 mm oduct size length oduct size height 1,106 m	D AND NOISE	
Signal Section	nt	146 kg
GINE tiput power (As rated by the engine/motor manufacturer) 5.5 kV tiput power 5.5 kV wer source Electri TOR Itage 400 V ted current 16 A INDING EQUIPMENT Inding width 250 m mber of grinding discs 1 inding disc speed max 1,920 HER pe of operation Push MENSIONS se diameter 76 mm adduct size length 1,301 m	ct size height	1,106 mm
S.5K 970 6 GINE Itput power (As rated by the engine/motor manufacturer) 5.5 kW wer source Electrications TOR Itage 400 V Itage 400 V Inding Equipment Inding width 250 m mber of grinding discs 1 Inding disc speed max 1,920 HER Pe of operation Push MENSIONS se diameter 76 mm	ct size width	458 mm
S.5K 970 6 GINE ttput power (As rated by the engine/motor manufacturer) ttput power ttput power wer source Electrical TOOR Itage ted current Inding EquipMent inding width mber of grinding discs inding disc speed max HER pe of operation Push	ct size length	1,301 mm
S.5K 970 6 GINE ttput power (As rated by the engine/motor manufacturer) ttput power ttput power 5.5 kV wer source Electr TOOR Itage 400 V ted current Inding Equipment inding width 250 m mber of grinding discs 1 inding disc speed max 1,920 HER pe of operation Push		76 mm
S.5K 970 6 GINE Itput power (As rated by the engine/motor manufacturer) 5.5 kW ttput power wer source Electr DTOR Itage 400 V ted current Inding Equipment inding width 250 m mber of grinding discs 1 Inding disc speed max 1,920		
S.5K 970 6 GINE Itput power (As rated by the engine/motor manufacturer) S.5 kW wer source Electrications TOR Itage 400 V ted current Inding Equipment inding width 250 m mber of grinding discs 1 inding disc speed max 1,920		Push
S.5K 970 6 GINE ttput power (As rated by the engine/motor manufacturer) 5.5 kW ttput power wer source Electrical stage ted current Inding width 250 m mber of grinding discs 1		
S.5K 970 6 GINE ttput power (As rated by the engine/motor manufacturer) ttput power ttput power 5.5 kW wer source Electrical TOTOR Itage 400 V ted current Inding width 250 m	ng disc speed max	1,920 rpm
S.5K 970 6 GINE ttput power (As rated by the engine/motor manufacturer) ttput power wer source Electrications TOR Itage ted current Inding Equipment	er of grinding discs	1
Signature Signat		250 mm
Signature Signat	ING EQUIPMENT	
GINE tput power (As rated by the engine/motor manufacturer) tput power tput power tput power Electrications 5.5 kW Electrications	current	16 A
Signary Signar	ge	400 V
Signary Signar	R	
SIGNE SIGNE STATE SPECIFICATIONS STATE SP	r source	Electric
SINE SPECIFICATIONS 5.5K 970 6	nt power	5.5 kW
5.5K 970 6	t power (As rated by the engine/motor manufacturer)	5.5 kW
ALL SPECIFICATIONS 5.5K	E	
RC 7		BG 250 3X400V 5.5KW 50HZ EU 970 61 49-01

× RELATED PRODUCTS AND ACCESSORIES

Recommended accessories that fit this model





MARSURF PS10









Accessory for Floor grinders

Accessory for Floor grinders

Accessory for Floor grinders

TEST EQUIPMENT Hardness test MOH's test kit



Accessory for Floor grinders

LOAD MORE (2)

X **SUPPORT**

Related support documents and downloads



DOCUMENT

OM. BG 250, BG 250PETROL. 2022-04

DOWNLOAD

DOCUMENTS

Didn't find your document?

GO TO SUPPORT SECTION

LEARN MORE ABOUT FLOOR GRINDERS



MAIN CATEGORY

ABOUT HUSQVARNA FLOOR GRINDERS

Learn more \rightarrow



MAIN CATEGORY

ABOUT HUSQVARNA SINGLE DISC FLOOR GRINDERS

<u>Learn more</u> →

PRODUCTS



GO TO FULL ASSORTMENT

DIAMOND TOOLS POWER CUTTERS CONCRETE CORE FLOOR SAWS TILE AND WALL SAWS WIRE SAWS

DRILLS MASONRY SAWS

YOU'RE AT HUSQVARNA CONSTRUCTION

Dealer locator

Contact us

Facebook
Instagram
LinkedIn
YouTube

Privacy notice

Terms of use

Cookie policy

Imprint

Report Suspected Violations

001

VIBRATORS

