

HUSQVARNA PG 5 S

HUSQVARNA INTRODUCES NEW PG 5 S FLOOR GRINDER

The PG 5 S is a compact and efficient planetary floor grinder with a focus on simplicity. The machine has three grinding discs and a 2.2-kW motor. It is suitable for many different flooring applications. For convenience, the chassis can be easily separated from the grinding head and the weights dismounted prior to transport. The dustproof design of the grinding head and electrical cabinet, along with the robustness of the components, contributes to high reliability and increased grinding precision.

Optional: Weights, water kit
Tool holder: EZchange™

FEATURES



SEALED TO LAST

Sealed grinding head with 1000 hrs service interval. No dust or water can intrude to damage components.



PROTECTED ELECTRONICS

Dust sealed electrical cabinet with external cooling technology. This prevents dust to intrude and damage components.



IMPROVED DUST PICK-UP

The robust steel floating shroud follows the floor surface for optimal dust pick-up — no adjustments needed.



TIME-SAVING TOOL CHANGE

EZchange™ is an instant and hassle-free system for changing diamond tooling. Tool holder plates are easily removed without the need of special tooling.

FEATURES

ADJUSTABLE GRINDING PRESSURE
The optional weights are a musthave for every professional grinder, as they allow to adjust the grinding pressure in three pre-set positions.

FITS INTO MOST STANDARD CARS
Split-chassis design with quick connectors makes transportation easy.

ERGONOMIC HANDLE
Adjustable handle for better ergonomics.

FLEET READY
Husqvarna Fleet Services™ is a digital, cloud-based asset management service that gathers and presents key machine data. Machine sensors are either embedded or retrofitted to the exterior of the machine.

TECHNICAL DATA HUSQVARNA PG 5 S

Art.no: 970 60 26-01 FLOOR GRINDER PG 5 S | 1 x 200-240 V | 2.2 kW | EU

ENGINE	
Rated input power	2.2 kW
Required current	13 A
Rated voltage	200–240 V
Frequency	50–60 Hz
Number of phases	1

GRINDING EQUIPMENT	
Working width	515 mm
Grinding speed	353–1176 rpm
Grinding pressure max.	80 kg
Number of grinding discs	3
Grinding discs diameter	230 mm
Mist / Weight	No / Optional
Dual drive	No
Remote controlled	No

DIMENSIONS & WEIGHTS	
Dimensions (L x W x H)	907 x 562 x 721 mm
Weight (without side packed article)	169 kg
Dust hose connection	50 mm

NOISE & VIBRATION	
Noise level at operators ear	73.8 dB(A)
Vibration level	Less than 2.5 m/s^2



RELATED EQUIPMENT & ACCESSORIES



WEIGHT KIT
Art. no: 597 51 27-01



WATER KIT
Art. no: 548 05 02-01



SOFT WHEELS
Art. no: 547 79 52-01



DE 130 H DUST EXTRACTOR
Art. no: 970 51 95-01



C 3000 PRE-SEPARATOR
Art. no: 967 66 45-01

RELATED DIAMOND TOOLS



G
ELITE-GRIND
Gold level series of tools with 6 different tools developed for concrete grinding. Sold as 3-pack.



G
ELITE-GRIND T-REX
Series of PCD (polycrystalline diamond) tools for efficient and fast removal of a range of coatings. Sold as 3-pack.



S
VARI-GRIND
Silver level series of tools with 3 different tools developed for concrete grinding. Sold as 3-pack.



G
ELITE-POLISH
Provides effortless and superior concrete polishing results.



S
VARI-POLISH
Designed to meet your polishing needs and tailored for dry or wet polishing processes.

Husqvarna®

husqvarnaconstruction.com

Copyright © 2024 Husqvarna AB (publ). All rights reserved. Husqvarna and other product and feature marks are trademarks of the Husqvarna Group or its licensors.
We reserve the right to make changes in technology and specifications without prior notice.