

# LED Light Arrow LP 13 Classic

- Electrically switchable to pointing left or right or to light cross
- Sandwich-Feature: Fitting of a second combinable Light Arrow LP 13 for routing of oncoming and following traffic
- Solid bracket for mounting on tubes
- Optional with cable remote control Eco-Remote II



**Light colour**  
yellow



**Eff. light intensity**  
1500 cd



**Max. light intensity**  
2200 cd



**Av. power consumpt. day**  
1.0 A



**Operating voltage**  
12/24V



**Weight**  
14 kg



**Dimensions (HxWxD)**  
900 x 900 x 155 mm

## LED Light Arrow LP 13 Classic

**Ref. No.**

LED Light Arrow LP 13 Classic  
consisting of:  
1 housing, made of highly weatherproof plastic  
with 13 LED lamps 200 mm Ø  
5 m connecting cable with battery clips

129 355-1

## Accessories and Spare parts

**Ref. No.**

Eco-Remote II cable remote control  
with 14 m cable and LP 13 holder  
Hand remote control LP13-Classik with 15m cable  
Adapter for mounting on board sides

129 266-53

329 300-01

329 365-1

## Operating time with one battery set

With rechargeable battery 12 V, 180 Ah

200 hrs

With rechargeable battery 12 V, 230 Ah

250 hrs



## More information

NIS-01331

To be entered on nissen-germany.com