

# LED Light Arrow LP 8

- Low wind load according to open design
- Continuous brightness adaptation
- Quick and easy mounting at or on vehicles and carriages
- Aluminium frame, slip-on type, for pointing left or right
- Bracket for mounting on tubes for manual setting to five different positions available



**Light colour**  
yellow



**Max. light intensity**  
2200 cd



**Eff. light intensity**  
1500 cd



**Av. power consumpt. day**  
1.3 A



**Operating voltage**  
12/24V



**Weight**  
13 kg



**Dimensions (LxWxH)**  
1130 x 900 x 165 mm

## LED Light Arrow LP 8

**Ref. No.**

LED Light Arrow Type LP 8  
consisting of:

129 361-152

8 Multi-Light 200 LED lamps 220 mm, mounted on an aluminium frame with slip-on device and 3 m connecting cable with battery clips

## Accessories and Spare parts

**Ref. No.**

Bracket for mounting on tubes with adjustment device, 5 positions

329 360-1

Adapter for mounting on board sides

329 365-3

## Operating time with one battery set

with rechargeable battery 12V, 56 Ah

50 hrs

With rechargeable battery 12V, 80 Ah

75 hrs

With rechargeable battery 12V, 180 Ah

160 hrs

With rechargeable battery 12V, 230 Ah

200 hrs



**More information**

NIS-00562

To be entered on nissen-germany.com