



**PM 100-130**



*- the safe way!*

## PM 100-130

### - Drop spreader series

The PM 100/130 is a small, compact, versatile, and efficient drop spreader designed for professional use in most weather conditions. It functions as both a salt and sand spreader, and is ideal for combating slippery conditions on smaller areas such as bicycle paths, footpaths, and other public spaces.

The PM 100/130 is not only versatile but also efficient in operation, ensuring fast and precise spreading of sand or salt. It is ideal for users who need to manage icy roads on small to medium-sized areas.

The machine is easy to mount and operate, and the spreader's distributor roller ensures precise and even distribution of the spreading material while the agitator prevents bridging and crushes any lumps in the material.

The simple design applies to both construction and daily use. The amount of material that is spread is regulated using a handle, which adjusts the tension of the spring base, and the spreader is immediately ready to use.



The spreading amount is regulated using a handle on the side of the spreader.



Hitch category 0/1.



The PM series is suitable for mounting on compact tractors and smaller carrying vehicles.

“

### Available with 3 operational modes:

- Hydraulic
- PTO
- Electrical

”

### The PM series offers three different operating modes:

#### Hydraulic operation:

Primarily used with tractors and requires correct oil pressure and flow. The spreader is activated by engaging the tractor's hydraulic outlet.

#### PTO operation:

Also common for tractors, where the user must ensure the correct rotation speed and direction of the PTO shaft. The spreader is activated by engaging the tractor's PTO output.

#### Electric operation:

A flexible solution compatible with all types of vehicles. This mode is operated via remote control and requires attention to the vehicle's voltage and current capacity.



Two different sizes of hopper for increased capacity.



Lights and reflectors for safer operation in the dark.



Tarpaulin to protect the spreading material when it rains or snows.

PM	100	130
Spreading width [m]	1	1,26
Hopper capacity [l]	120	150
Height* [mm]	515	515
Total length [mm]	610	610
Total width [mm]	1115	1415
Hopper width [mm]	1060	1360
Deadweight* [kg]	110	126
Hopper extension frame [l]	50-100	75-150
Operational mode	PTO, Hydraulik, Electrical (12V)	PTO, Hydraulik, Electrical (12V)
Min. quantity oil [l/min.]	18	18
Min. oil pressure [bar]	100	100

\*Dependent on configuration

## EPOKE GROUP

We produced our first sand and salt spreader in 1955, and since then we have solely focused on the development, production and sale of machines and equipment for the treatment of icy roads. Today, we are a global leader. In Denmark, sales are carried out by our own sales staff, while abroad our subsidiaries and 31 dealers manage sales.

Learn more at [www.epoke.dk](http://www.epoke.dk)

Epoke A/S  
 Vejervej 50  
 6600 Vejen  
[www.epoke.dk](http://www.epoke.dk)

