

MonoLight LED

- High-quality LEDs with nearly unlimited life time
- Only one battery needed
- Lamp head adjustable, with reflective rim
- Automatic solar switch
- Optional with firmly mounted bracket for attachment to vertical tubes



Light colour amber resp. red	Eff. light intensity two-sided 15 cd / omnidirectional 3 cd	Blink-/flash rate 60 - 70 fl./min.	Light source 1 LED
Dimensions (WxH) without bracket 185 x 120 x 340 mm	Weight 0.5 kg without bracket 0.6 kg with bracket		



MonoLight omni-directional



MonoLight with bracket



NiKo key



Changing battery

MonoLight LED	Ref. No.
MonoLight LED, flashing/steady light, two-sided amber, with bracket	111 602-51
MonoLight LED, flashing/steady light, two-sided red, with bracket	111 602-53
MonoLight LED, flashing/steady light, two-sided amber, without bracket	111 602-1
MonoLight LED, flashing/steady light, two-sided red, without bracket	111 602-3
MonoLight LED, flashing/steady light, omni-directional amber, without bracket	111 605-1

Accessories and Spare parts	Ref. No.
Bracket for mounting the MonoLight and BakoLight	070 877 1
NiKo key	070 090-11
NiKo bracket for mounting the MonoLight on barriers	365 5191
Bracket for mounting the MonoLight / SignLite on traffic cones	292 032-31

Operating time with one battery set	
With battery Premium 800	steady light 300 hrs flashing light 1200 hrs
With battery Konstant 45	steady light 1400 hrs flashing light 5500 hrs

Packaging
20 pcs in one carton / 400 pcs on one pallet
also available in other quantities

More information
NIS-00216
To be entered on nissen-germany.com