

# MonoLight LED

- High-quality LEDs with nearly unlimited life time
- Only one battery needed
- Lamp head adjustable, with reflective rim
- Automatic solar switch
- Optional with firmly mounted bracket for attachment to vertical tubes



**Light colour**  
amber resp. red



**Eff. light intensity**  
two-sided 15 cd /  
omnidirectional 3 cd



**Blink-/flash rate**  
60 - 70 fl./min.



**Light source**  
1 LED



**Dimensions (WxH)**  
without bracket  
185 x 120 x 340 mm



**Weight**  
0.5 kg without bracket  
0.6 kg with bracket



MonoLight omni-directional



MonoLight with bracket



NiKo key



Changing battery

## MonoLight LED

## Ref. No.

MonoLight LED, flashing/steady light, two-sided amber, with bracket	111 602-51
MonoLight LED, flashing/steady light, two-sided red, with bracket	111 602-53
MonoLight LED, flashing/steady light, two-sided amber, without bracket	111 602-1
MonoLight LED, flashing/steady light, two-sided red, without bracket	111 602-3
MonoLight LED, flashing/steady light, omni-directional amber, without bracket	111 605-1

## Accessories and Spare parts

## Ref. No.

Bracket for mounting the MonoLight and BakoLight	070 877 1
NiKo key	070 090-11
NiKo bracket for mounting the MonoLight on barriers	365 5191
Bracket for mounting the MonoLight / SignLite on traffic cones	292 032-31



**Packaging**  
20 pcs in one carton / 400 pcs on one pallet  
also available in other quantities



**More information**  
NIS-00216  
To be entered on nissen-germany.com

## Operating time with one battery set

With battery Premium 800	steady light 300 hrs flashing light 1200 hrs
With battery Konstant 45	steady light 1400 hrs flashing light 5500 hrs