

# Twofold Warning System Zyklop 220 LED Flash L8M

- Energy-efficient design with only one LED
- Automatic day/night adaptation
- 5 m connecting cable with battery clips
- Consisting of one master lamp and one slave lamp, cable length between the lamps ca. 3 m
- Approved according to EMC directive



**Light colour**  
yellow



**Eff. light intensity**  
500 cd



**Av. power consumpt. day**  
0.06 A



**Operating voltage**  
12/24 V



**Blink-/flash rate**  
60 fl./min.



**Light source**  
1 LED



**Weight**  
1.2 kg/set

## Twofold Warning System Zyklop 220 LED Flash L8M

**Ref. No.**

Twofold Warning Light System Zyklop 220 LED Flash L8M  
type 671/F NiBus, 12/24 V, with 5 m connecting cable with battery clips

122 222-201

## Accessories and Spare parts

**Ref. No.**

Box for rechargeable batteries 12 V up to 230 Ah, lockable  
Bracket for tubes up to 82 mm

190 230-1  
365 522-12

## Operating time with one battery set

With rechargeable battery 12 V, 100 Ah

1500 hrs



Twof. system Multi-Light 220 LED Flash L8M



Twofold Warning System with bracket



Box for rechargeable batteries



**More information**

NIS-01329

To be entered on nissen-germany.com