



THE TP SERIES

Spreading disc, roller and spray boom spreaders



- the safe way!

The TP Series

TP Series spreaders are hitched tractor spreaders that spread grit, sand, salt and liquid using a roller, spreading disc or spray boom.

TP Series spreaders have a simple and service-friendly design, which makes them easy to use and maintain. This results in greater user satisfaction, low operating costs and a long product lifetime. The spreaders are available in variants TP1,5, TP3, TP3 Combi and TP9.

Using Epoke's dosing principle, via the spray boom or directly via the spreading disc, the TP spreaders spread the material in widths of 1.5–6 m, depending on the model. This means TP spreaders are ideal for smaller roads, bicycle paths and car parks.

TP spreaders ensure that the spreading material is spread with an even and uniform spreading profile. At the same time the spreader is width, amount and speed-compensated. This means that the set spreading amount per m² is constant, regardless of changes in the spreading width or the vehicle's speed.

TP spreaders are operated as standard using Epoke's compact, simple and user-friendly remote control, EpoMini X1, and Epoke's data collection solution can also be purchased.

TP3 and TP9 can also be equipped with the GPS control system EpoSat and with the advanced remote control EpoMaster X1.

The dry matter hopper is sandblasted and coated with a 2-component zinc primer and 2-component topcoat and thus the spreader is well protected against corrosion.

- The dry matter hopper is available in sizes from 200 l to 1500 l
- The agitator in the dry matter hopper prevents bridging
- The liquid tank is made from PVC, which can tolerate aggressive liquids
- Uses well-known components
- Easy to change between roller or spreading disc operation
- Speed-compensated spreading
- Full control of the spreading process using the remote control
- SH or PTO operation as required and depending on the model
- Data collection and GPS control can be purchased



The Epoke dosing principle with distributor roller and agitator.



Easy-to-use, foldable tarpaulin.



Remote controls: EpoMini X1 and EpoMaster X1.

	Technical data			
	TP1,5	TP3	TP9	TP3 Combi
Dry matter hopper, l	200	300	900	300
Hopper extension frame, l	100	100/200/300	300/600	100/200/300
Total width, mm	1100	1300	2100	1300
Spreading width, spreading disc, mm	1500–4000	1500–6000	1500–6000	1500–6000
Spreading width, roller, mm	800	1200	1800	1200
Weight, kg	180	315	435	430
Is fitted to tractor with minimum weight, kg	800	1000	3000	1000
Operating power	Hydraulic	Hydraulic/PTO		Hydraulic
Three-point hitch, category	0 + 1	1 + 2	2 + 3	1 + 2
Hydraulic system, minimum oil flow, l/minute	25			25
Oil pressure, bar, max.	180			
Liquid tank volume, l	-	200/300	500	300



TP3 Combi



TP9



TP3 Combi with spray boom for liquid application.



Spreading disc with spreading width of 1.5–6 m.



Electrical emptying function.

Epoke Group

We produced our first sand and salt spreader in 1955, and since then we have solely focused on the development, production and sale of machines and equipment for the treatment of icy roads. Today, we are a global leader. In Denmark, sales are carried out by our own sales staff, while abroad our subsidiaries and 31 dealers manage sales.

Learn more at www.epoke.dk

Epoke A/S
Vejenvej 50
6600 Vejen, Denmark
www.epoke.dk

