



### FLEXMATIC+

The FlexMatic+ is the ideal spring machine for professional cleaning of drains and sewers between 12 - 75 mm diameter. The lightweight and compact design in addition to the flexible adapter hose makes it easy to handle and maneuver in narrow spaces.

The automatic spring feed unit has large roller bearings for long term use. It is easy to operate by pushing the handle forward and back to drive the spring in and out of the drain. The spring rotates in neutral position. The flexible adapter hose is ideal for narrow spaces.

The air activated foot switch turns the machine on and off which leaves both hands free for working. The springs have coiled bulbous heads. The 10 mm springs have the unique Rioned square coupling system allowing different kinds of tools to be used.



Practical automatic spring feed unit

| TECHNICAL SPECIFICATIONS |                         |
|--------------------------|-------------------------|
| Motor                    | 110, 230 Volt / 0,18 kW |
| Ø Drain/sewer            | 12 mm - 75 mm           |
| Ø Spring                 | 6 - 8 - 10 mm           |
| Spring length            | 7,5 - 10 - 15 m         |
| Weight incl. spring      | 12 kgs                  |
| Maximum Dba              | 69                      |
| Accessories/tools *      | 1 - 4 - 5 - 8 - 9 - 11  |

\* See page 42 and 43 for a description



Integrated drawer for accessories