

Husqvarna W 250 P

W 250 P is a small powerful industrial wet and slurry vacuum designed for tough jobs. This is achieved by using high quality stainless steel components and a powerful motor protected by a float. Recommended for concrete drilling, sawing, grinding and general slurry collection. Ingenious solutions make W 250 P easy to work with. Pumping out can take place at the same time as suction. The non-marking wheels are puncture-free and lock at the front.

- Phases **1~**
- Air Flow **160 m³/h**
- Rated input **1.55 kW**
power

Article number : SLURRY VACUUM W 250 P

230 V | 1-ph | EU - 967 70 21-02



FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



Renowned durability

Stainless steel container, crush-proof hose, cast aluminium swivel hose lock, galvanized steel dolly and steel clamps for tight air seal are details allowing for a long service life.



Reliable overfill shut-off

The patented filter/float system provides maximum airflow and reliable wet shut-off in case of overfill.

High pumping pressure

The powerful evacuation pump is capable of pumping the slurry 6 meters vertically or 150 meters horizontally.



Integral stainless steel strainer


Screens gravel from the slurry to protect the pump impeller.



SPECIFICATIONS



Phases	1~
Voltage	230 V
Rated current	5,2 A
Max. vacuum	220 mbar
Rated input power	1.55 kW



Product size height	910 mm
Product size length	530 mm
Product size width	520 mm

Specifications

Air Flow	160 m³/h
Max. vacuum	220 mbar