

Warning Trailer

B2



CHASSIS AND BODY

- Chassis and body of galvanized steel
- Galvanized, height-adjustable drawbar (Al-Ko), with overrun brake, holding brake and parallel adjustment
- DIN towing eye and with a changeable spherical head coupling
- Loading area of 15 mm 7 layered laminated plywood sheets with sealed edges
- Side panels of 15 mm 7 layered laminated plywood covered with aluminium sheet profil at the top
- Height-adjustable semi-automatic support wheel
- Robust plastic fenders
- Battery box integrated into the side panel design incl. cover of aluminium chequered plate (1000 x 400 x 300 mm)
- Braked rubber spring axle
- 4 lashing points (straps) with 400 daN
- 2 fully adjustable support legs

WARNING BOARD

- Warning board in compliance with RSA 95 and ZTV-SA incl. traffic sign 616-31 StVO (road traffic regulations), 2500 x 1700 mm
- Chevron patterned plates and directional arrow with microprismatic retro-reflective foil, type RA2C
- Luminous arrow system with two LED-TL advance warning beacons (WL5) and 15 separately monitored LED-TL warning beacons (WL6)
- Directional arrow with motor revolution, mechanical emergency adjustment and automatic luminous arrow adjustment
- Motorized lifting and lowering of the top board with mechanical emergency adjustment and freely accessible emergency-off switch
- Manual cable or radio control for operating all functions via one-touch keys

ELECTRICAL SYSTEM

- Rechargeable battery 12 V, up to 55 hours daytime operation (further energy packages on request)
- Trailer lighting optionally 12 V or 24 V
- Feed socket 230 V



ACCESSORIES AND OPTIONS

- Battery guard for protection of electronics
- Cargo securing set
- Central crank supports
- Control and monitoring system
- Optionally warning board Z615

Technical data

Total length	4200 mm
Total width	1700 mm
Track width	1400 mm
Loading area (LxW)	1750 x 1050 mm
Total weight	300 kg
Empty weight depending on model	750 - 1000 kg
Track width	400 kg
Max. load capacity	350 - 600 kg

Warning Trailer Type B 2

Warning Trailer Type B 2, without light warning system

Ref. No.

129 700-002