

TEMPO TP temporary marking spray paint



Product codes:

Reference: 141618

EAN13: -

UPC: -

Product attributes:

Color: White, Red, Orange, Yellow, Green, Blue, Cherry

Volume: 500 ml

Product features:

Product Type: Temporary Marking Spray

Type of paint: Fluorescent paint

Marking time: 2 months

Volume: 500 ml

Packaging: 12 per box

Brand: SOPPEC

Product short description:

TEMPO TP is a temporary marking paint that is used for short term marking (2-8 weeks). This Chalk-based product is erasable under mechanically means (water spray, low pressure cleaner, brushes...). This easily allows its use on classified or protected areas, for urban environment, for landscaping plan. Easy and safe to use, TEMPO TP is fitted with the patented Soppec «TP» safety spray cap.

Product description:

TEMPO TP : THE IDEAL MARKING SPRAY PAINT
FOR FLUORESCENT AND TEMPORARY MARKINGS

Properties of the TEMPO TP temporary marking paint

- Excellent adhesion on various surfaces: bitumes, grass, concrete, sand (for others surfaces test before use)
- Highly visible from afar
- A particularly robust safety cap (a full aerosol dropped from a height of 1.50m will remain intact).
- Quick drying: 10 mn
- Use temperature range: -20 to 50°C
- Short marking duration including on damp surfaces, of up to 8 weeks depending on the surface, the conditions of application and UV exposure
- Product available in a large wide of colours
- Aerosol cans, gross volume 650 ml, net volume 500 ml, in boxes of 12

Specifications of the TEMPO TP temporary spray marker

Composition

Binder: complex blend of mineral oils and clays.

Pigments: mineral and organic, free from heavy metals.

Solvents: complex blend free from chlorinated solvents and aromatic compounds.

Propellant: specific blend of isobutane and propane.

Application method

Manually or using our purpose-designed application equipment (See bellow).

BEFORE USE: shake vigorously head down.

AFTER USE: purge head up.

Health and safety

No paint mist or drips during use.

CLP labelling with two pictograms.

DANGER

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Safety Data Sheet

GET THE SAFETY DATASHEET