

Twofold Warning System 340 LED L9H

- Energy-efficient LED technology
- Automatic day/night adaptation, switchable to solar switch
- Consisting of one master lamp and one slave lamp, cable length between the lamps 6 m
- Master lamp with 5 m connecting cable with battery clips



| | | | |
|----------------------------------|--------------------------------------|----------------------------------|------------------------------|
| Light colour yellow | Eff. light intensity day 20000 cd | Av. power consumpt. day 0.8 A | Operating voltage 12/24 V |
| Blink-/flash rate 60 fl./min. | Light source 4 LED | Weight 5.4 kg/set | |

| Twofold Warning System Multi-Light 340 LED L9H | Ref. No. |
|--|-----------|
| Twofold Warning Light System Multi-Light 340 LED L9H Type 690/1 NiBus, 12/24 V, with 5 m connecting cable with battery clips | 122 312-1 |
| Accessories and Spare parts | Ref. No. |
| Box for rechargeable batteries 12 V up to 230 Ah, lockable | 190 230-1 |
| Operating time with one battery set | |
| With rechargeable battery 12 V, 180 Ah | 350 hrs |
| With rechargeable battery 12 V, 100 Ah | 150 hrs |



Twofold Warning S. Multi-Light 340 LED L9H



Twofold Warning System with bracket



Box for rechargeable batteries

More information
NIS-00546
To be entered on nissen-germany.com