

# Twofold Warning System Zyklop 220 LED L8H

- Energy-efficient design with only one LED
- Automatic day/night adaptation, switchable to solar switch
- 5 m connecting cable with battery clips
- Consisting of one master lamp and one slave lamp, cable length between the lamps ca. 3 m



<b>Light colour</b> amber	<b>Eff. light intensity</b> 1500 cd	<b>Av. power consumpt. day</b> 0.28 A	<b>Operating voltage</b> 12/24 V
<b>Blink-/flash rate</b> 60 fl./min.	<b>Light source</b> 1 LED	<b>Weight</b> 1.2 kg/set	

Twofold Warning System Zyklop 220 LED L8H	Ref. No.
Twofold Warning Light System Zyklop 220 LED L8H Type 671/1 NiBus, 12/24 V, with 5 m connecting cable with battery clips	122 222-1
Accessories and Spare parts	Ref. No.
Box for rechargeable batteries 12 V up to 230 Ah, lockable	190 230-1
Bracket for tubes up to 82 mm	365 522-12
Operating time with one battery set	
With rechargeable battery 12 V, 100 Ah	440 hrs
With rechargeable battery 12 V, 180 Ah	800 hrs
With rechargeable battery 12 V, 230 Ah	1000 hrs



Twofold Warning System Zyklop 220



Twofold Warning System with bracket



Box for rechargeable batteries

**More information**  
NIS-01411  
To be entered on nissen-germany.com